

## Overview

Our Flush Stainless Steel Enclosures are specifically designed for either indoor or outdoor applications, these enclosures combine a rugged continuous hinge, seamless foam-in-place gasket and stainless steel screw-down clamps for a reliable seal that protects components from corrosive environments. Our enclosures are able to house PLC's, gateways, fuse blocks, din-mounted power supplies, pressure transducers and other I/Os. Our enclosures are supplied seamless, ready for conduit and wireway holes to be drilled.



## Main Features and Specifications

- Rugged hinge and stainless steel screw down clamps
- Seamless foam-in place gasket
- Smooth brushed finish
- 16 and 14 gauge Type 304 or 316L stainless steel.
- Seams continuously welded and ground smooth
- Seamless foam-in-place gasket.
- Stainless steel screws and clamps
- Pull stainless steel continuous hinge pin to remove door
- Weldnuts provided for mounting optional panels and terminal block kits
- Bonding provision on door and body
- Cover and sides of body have smooth #4 brushed finish.

## Available Sizes

- ACP NL06, 14x12x6 - accommodates all AirCare Consoles and Gateways

## Industry Standards

- UL 50, 50E Listed; Type 3R, 4, 4X, 12; File No. E27567
- cUL Listed per CSA C22.2 No 94; Type 3R, 4, 4X, 12; File No. E27567
- UL 508A Listed; Type 3R, 4, 4X, 12; File No. E61997
- cUL Listed per CSA C22.2 No 94; Type 3R, 4, 4X, 12; File No. E61997
- NEMA/EEMAC Type 3R, 4, 4X, 12, 13
- CSA File No. 42184: Type 4, 4X, 12
- IEC 60529, IP66
- Meets NEMA Type 3RX requirements

### ACPNL06 14x12x6 Mechanical Dimensions

